

Declaration of performance (DOP)

H 570 T



Product type	Insert
Type	H 570 T-CPR-2015/03/18
Serial number	See EN-label
Intended use of the product	Room heater, without hot water supply
Fuel	Solid fuel
Manufacturer	Lotus Heating Systems A/S
Address of the manufacturer	Agertoften 6 5550 Langeskov DK
System of assessment and verification of constancy of performance of the product. AVCP	System 3
Harmonized technical specification	EN EN 13 229: 2001 /A2:2004/AC:2007
Notified Laboratory	Reihn-Ruhr Feuerstätten Prüfstelle, 1625 Test report: RRF-29 08 1600

Declared performance

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	A1 WT	
Distance to combustible materials	Minimum distance rear: 800mm Sides: Outside insulation 0mm Front: 800 mm	
Risk of burning fuel falling out	Pass	
Emission of combustion products	CO: 0,10 % CO: 1250 mg/Nm ³ Dust: 29 mg/Nm ³ Dust NS: g/kg dried wood OGC: 51 mg/Nm ³ NOx: 86 mg/Nm ³	EN EN 13 229: 2001 /A2:2004/AC:2007
Surface temperature	Pass	
Cleanability	Pass	
Mechanical resistance(carry a flue)	Pass	
Risk of fuel falling out	Pass	
Nominal heat output	6 KW	
Energy efficiency	80,4 %	
Flue gas temperature at nominal heat output	310 °C	

Signed for and on behalf of the manufacturer by.

Johnny Ebstrup, CEO Lotus Heating Systems A/S

