CADEL

INFORMATION REQUIREMENTS FOR SOLID FUEL LOCAL SPACE HEATERS ACCORDING TO COMMISSION REGULATIONS (EU) 2015/1185 - (EU) 2015/1186 (PRODUCT FICHE)

Models	ZEFIRO 9 T2
Intended use of the product:	Mechanically fed inset fitted with a boiler burning wood pellets
Manufacturer	Cadel srl - Via Martiri della Libertà, 74 - 31025 S. Lucia di Piave (TV) - Italia
Trade mark	CADEL
AVCP system	System 3
Notified body	NB 0476
Test report number	2013909
Harmonised technical specification	EN 16510-1:2022 / EN 16510-2-6:2022

ESSENTIAL CHARACTERISTICS

Fuel	Log wood, moisture content ≤ 25 %			No	
	Compressed wood with moisture content < 12 %			Yes	
Type of heat output/room temperature control (select one)	Single stage heat output, no room temperature control			No	
	Two or more manual stages, no room temperature control			No	
	With mechanic thermostat room temperature control			No	
	With electronic room temperature control			No	
	With electronic room temperature control plus day timer			No	
	With electronic room temperature control plus week timer			Yes	
Other control options (multiple selections possible)	Room temperature control, with presence detection			No	
	Rroom temperature control, with open window detection			No	
	With distance control option			Yes	
Performance - Emissions	No	Symbol		Nominal power	Reduced power
	Carbon monoxide emissions (CO at 13% O2)	COnom	COpart	125 mg/Nm³	140 mg/Nm³
	Emission of nitrogen oxides (NOX at 13% O2)	NOxnom	NOxpart	99 mg/Nm³	120 mg/Nm³
	Emission of organic gaseous compounds (OGC at 13% O2)	OGCnom	OGCpart	2 mg/Nm³	2 mg/Nm³
	Particulate matter emissions (PM at 13% O2)	PMnom	PMpart	15 mg/Nm³	20 mg/Nm³
Performance - Power and efficiency	Heating power to the environment	Pnom	Ppart	9,0 kW	3,5 kW
	Heating power to the water	Pwnom	PWpart	/	/
	Efficiency - Useful efficiency	ηnom	ηpart	90 %	91 %
Space heating efficiency	Seasonal energy efficiency	ηs		85 ηs [%]	
	Energy efficiency index	EEI		126	
	Energy efficiency class (A++ / G scale)	-		A+	
Auxiliary electricity consumption	Electrical consumption at nominal heat output	elmax		0.114 kW	
	Electrical consumption at partial load heat output	elmin		0.040 kW	
	Electrical consumption in standby mode	elSB		0.001 kW	
Sealed Chamber	Appliance Type (tightness)	Type		CC50	

Observe the specific precautions for installation, assembly and maintenance indicated in the manual accompanying the product, and the national and local rules in force

CADEL s.r.l.
Via Martiri della Libertà, 74
31025 SANTA LUCIA DI PIAVE (TV)
Tel. 0438 1520200 - Fax 0438.73343
Partita IVA 03202180265
R.E.A. TV 227665 - Reg. Soc. Trib. TV 185949

Santa Lucia di Piave, 06/06/25

Dassie Roberto (R&D Manager)